

Predictive Digital Thermometer



KD-192

Specifications

Model	KD-192
Measuring Range	30.5°C ~ 43.9°C(86.9°F~111.1°F)
Resolution	0.1°C (0.1°F)
Accuracy	±0.2°C (±0.4°F) as Temperature < 34.0°C(93.2°F) ±0.1°C (±0.2°F) as Temperature between 34.0°C ≤ T ≤ 42°C (93.2°F ≤ T ≤ 107.6°F) ±0.2°C (±0.4°F) as Temperature > 42.0°C(107.6°F)
Display	Liquid Crystal Display 3 1/2 digits
Operation Condition	Temperature: 10 to 40°C (50 to 104°F) Relative Humidity: 15 to 95 %
Storage Condition	Temperature: -20 to 50°C (-4 to 120°F) Relative Humidity: 15 to 95 %
Battery	Micro Alkaline 186 or LR 43 (1.55V) x 2
Power Consumption	6.0 milliwatt per measurement
Low Battery indication	Replace the batteries if the low battery indicator appears
Auto Off	Automatically after 30-second of non-use
Size	124 x 23.7 x 13 mm
Weight	Approx. 14 grams including battery
Standard	Complies with EN 12470-3 and ASTM E 1112-00

Specifications are subject to change for improvement without notice.

Accessories:

- Storage Case
- Probe Cover (optional)

K-jump Health Co., Ltd.

No. 56, Wu Kung 5th Rd., New Taipei Industrial Park,
New Taipei City 24890, Taiwan

Tel: 886-2-22991378 Fax:886-2-22991386

E-mail: service@kjump.com

<http://www.kjump.com>



CE 0197

Features:



Quick Read



Memory



Beeper



Fever Alarm



Three Mode Selection



Tip waterproof

Optional Functions:



Flexible Tip



C/F Switchable

